Rugged Industrial PDA 4.3" E430RT-BMM



Product Features:

- 4.3" 480x800 Panel with Projective Capacitive Multi-touch.
- · Built-in Wi-Fi/ Bluetooth/ GPS / Optional 3G Communication
- · 5 Mega-pixel camera with LED at rear side
- · Built in Motorola SE4500 1D/2D Barcode Reader.
- · Water and dust proof ID IP65 design
- · Compliance with MIL-STD-810G for High/Low temperature, Vibration, Drop test
- Support Windows Embedded Handheld 6.5 operating system







2D Scanner Engine

Sym	mbologis				
2D	QR Code, Data Matrix, PDF417, Maxicode, Aztec				
1D	UPC/EAN, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, Postal codes, GS1 DataBar, Composite				

Order Information:

	Model Name	Configuration
	E430RT-BMM	no 3G+ 1D/2D barcode + WEH 6.5
	F430RT-3BMM	3G+ 1D/2D barcode + WEH 6.5

Product Specifications:

	Processor	11 Cortex A8 OMAP DM3730 1GHz
System	System Memory	512MB SDRAM
Specification	Storage	512MB NAND flash
	Operating System	WEH 6.5
	Size	4.3"
Display	Resolution	480 x 800
Specification	Brightness	400(typ.)
	Touch	Projective Capactive Multi-touch
	WLAN	802.11 b/g/n
Wireless	Bluetooth	Bluetooth V2.1+EDR
Communication	WWAN	GSM / GPRS / EDGE / WCDMA / HSDPA / HSUPA (optional; for data Transmission)
	GPS	Built-in GPS module
	Dimensions (W x L x H)	132.2 x 82 x 25.7 mm
	Weight	260g
	Operation Temperature	-20 °C to 60 °C(AC Mode) -10 °C to 50 °C(Battery Mode)
Mechanical and Environment	IP Proof	IP65
Environment	Shock	Shock MIL-STD-810G M516.5
	Vibration	Vibration MIL-STD-810G M514.5
	Drop	MIL-STD-810G M516.5, 4 ft, Free to concrete
	Certifications	CE, FCC,UL
	External I/O	1 x Micro USB
	Internal I/O	1 x SIM card slot
	Internal I/O	1 x Micro SD card slot
I/O Connectors	Data Capture	1 x 1D / 2D Barcode Reader
		1 x Microphone
	Internal Audio Device	1 x Earphone
	Internal / todal o Dovido	1 x Speaker
	Control button	1 x Volume - +
		1 x Power button
In front Control		1 x Function button
		4 x Capactive buttons:Home/ Menu/ ESC/ Search functions
	LED indicator	1 x LED indicator
Field Centic	Main Camera (Rear)	5 Mega-Pixel Camera with LED auxiliary light
Field Service	Light Sensor	Built-in
	Proximity (Light) Sensor	Built-in 3.7V 3900mAh Li-poly rechargeable battery
Dower	Battery Operating Time	10Hr *
Power	Battery Operating Time	
	Adapter	5V 1A Adapter

TI Cortex A8 OMAP DM3730 1GHz

*Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.

Drawing









