Rugged Industrial PDA 4.3"

Product Features:

- · Projective Capacitive Multi-touch.
- Built-in Wi-Fi/ Bluetooth/ GPS / Optional 3G Communication
- 5 Mega-pixel camera with LED at rear side
- Water and dust proof ID IP65 design
- Compliance with MIL-STD-810G for High/Low temperature, Vibration, Drop test
- · Support Windows Embedded Handheld 6.5 operating system

Product Specifications:

System Specification	Processor	TI Cortex A8 OMAP DM3730 1GHz
	System Memory	512MB SDRAM
	Storage	512MB NAND flash
	Operating System	WEH 6.5
Display Specification	Size	4.3"
	Resolution	480 x 800
	Brightness	400(typ.)
	Touch	Projective Capacitive Multi-touch
Wireless Communication	WLAN	802.11 b/g/n
	Bluetooth	Bluetooth V2.1+EDR
	WWAN	GSM / GPRS / EDGE / WCDMA / HSDPA / HSUPA (optional ; for data Transmission)
	GPS	Built-in U-Blox GPS module
	Dimensions (W x L x H)	132.2 x 82 x 21.5 mm
	Weight	220g
	Operation Temperature	-20 deg.C to 60 deg.C(AC Mode) -10 deg.C to 50 deg.C(Battery Mode)
	Charging Temperature	50° ~ 113°F / 10° ~ 45°C
Mechanical and	Operation Humidity	95% RH, non-condensing
Environment	IP Proof	IP65
	Shock	Shock MIL-STD-810G M516.6
	Vibration	Vibration MIL-STD-810G M514.6
	Drop	MIL-STD-810G M516.6, 4 ft, Free to concrete
	Certifications	CE, FCC,CCC,UL
	External I/O	1 x Micro USB
		1 x 3.5mm Audio jack for microphone and headset
		1 x SIM card slot
I/O Connectors	Internal I/O	1 x Micro SD card slot
	Internal Audio Device	1 x Microphone
		1 x Earphone
		1 x Speaker
Dedicated keys	Control button	1 x Volume +
		1 x Volume -
		1 x Power button
		1 x Function button
		4 xCapacitive buttons:Home/ Menu/ ESC/ Search
	LED indicator	1 x LED indicator
Field Service Feature	Main Camera (Rear)	5 Mega-Pixel Camera with LED auxiliary light
	Light Sensor	Built-in
	Proximity (Light) Sensor	Built-in
i catare		
roduro	Battery	3.7V 2600mAh Li-poly rechargeable battery
Power	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	3.7V 2600mAh Li-poly rechargeable battery 9Hr *

Start Start WWW WWW WWW WWW WWW WWW WWW Surpert Surpert

E430T-M



Order Information:

Model Name	Configuration
E430T-M	No 3G+ WEH 6.5
E430T-3M	3G+ WEH 6.5

*Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.

Drawing

WINMATE











